THINNER RO 10455

Type	Mixture of aromatic hydrocarbons and glycol ethers
Uses	It is a paint thinner. Designed to improve the flow of a range of epoxy products. Can also be used as cleaner for pumps and tools before and after painting.
Appearance	clear
Density	0.76 ± 0.02 g/cm^3
Flash point	30 °C
Flammability	This material is flammable and should be handled with care, keep material away from sources of ignition and take necessary precautions against static discharge
Boiling point	120 °C – 145 °C
Pack size	25 ltr – 200 ltr
Storage	In original tightly closed containers, in a cool, well ventilated place at temperature between 5 °C and 40 °C.
Shelf life	3 years when stored in accordance with the above storage instructions.

Roots
Paints & Chemicals
روتس للبويات والصناعات الكيماوية
شركة مساهمة مصرية

شركة روتس للبويات والصناعات الكيماوية
Roots company for Paints & Chemicals industries

الإدارة : ٥٢ شارع دمشق - المهندسين تليفاكس : ٠٢٣٣٣٧٣٨٠٤ المصانع : السادس من اكتوبر - المنطقة الصناعية الاولى خدمة عملاء : ٠١٠٠٣٤٢١٢٢٣
www.rootspaints.com info@rootspaints.com

Safety precautions

During application of products using this thinner ensure normal safety practices such as wearing of protective gloves, face mask and eye protection. When used in confined spaces self contained breathing apparatus should be worn .Avoid breathing vapor and ensure adequate ventilation during use

Inhalation :

Remove subject to fresh air immediately and if breathing is difficult, seek medical advice

Skin contact :

Contaminated clothing should be removed and skin washed thoroughly with soap and water

Eye contact :

Rinse with plenty of fresh, clean water for 15 minutes and keep eyes open. If irritation persists, seek medical attention.

Ingestion :

If swallowed, rinse mouth with fresh water and give water to drink seek immediate medical attention or transport to hospital

Roots
Paints & Chemicals
روتس للبويات والصناعات الكيماوية
شركة مساهمة مصرية

شركة روتس للبويات والصناعات الكيماوية
Roots company for Paints & Chemicals industries

الإدارة : ٥٢ شارع دمشق - المهندسين تليفاكس : ٠٢٣٣٣٧٣٨٠٤ المصانع : السادس من اكتوبر - المنطقة الصناعية الاولى خدمة عملاء : ٠١٠٠٣٤٢١٢٢٣
www.rootspaints.com info@rootspaints.com